



T8 HB LED Tubes



The Light Footprint T8 LED tubes utilises the latest High Brightness SMD chip technology to maximise light output, while incorporating a shatterproof polycarbonate opal lens and adjustable end caps to allow for optimal diffusion and directional control.

Produced to the highest specifications our tubes have as standard, built-in high power factor isolated drivers to maximise tube efficiency combined with total in-rush protection to safeguard vital components from power surges, over-load and over-heat protection. Using single sided power (SSP) and non-conductive end caps ensures simple and safe installation.

*Please see T8 installation guide for rewiring instructions.

Technical Specification

Total Circuit Wattage 10W/14W/18W
23W/28W/36W

Working Voltage 100-265VAC

Working Temperature -30°C/+45°C

Beam Angle 140°

Estimated Life Span 50,000hrs

CRI >80

Lamp Base Rotatable G13

Power Factor >0.96

Test Standards

EN55015:2006+A1:2007+A2:2009

EN61547:2009

EN61000-3-2:2006+A1:2009+A2:2009

EN61000-3-3:2008

EN60598-1:2008+A11:2009



5 Year Warranty **LM 80**

Product Code	Size	Colour	Lumen	TCW	Dimmable
FR600FRNW	588mm (2ft) x 26mm	Natural White 4500K (NW)	855	10W	Optional
FR600FRDW	588mm (2ft) x 26mm	Daylight White 5500K (DW)	900	10W	Optional
FR900FRNW	891mm (3ft) x 26mm	Natural White 4500K (NW)	1090	14W	Optional
FR900FRDW	891mm (3ft) x 26mm	Daylight White 5500K (DW)	1150	14W	Optional
FR1200FRNW	1198mm (4ft) x 26mm	Natural White 4500K (NW)	1630	18W	Optional
FR1200FRDW	1198mm (4ft) x 26mm	Daylight White 5500K (DW)	1715	18W	Optional
FR1500FRNW	1496mm (5ft) x 26mm	Natural White 4500K (NW)	2040	23W	Optional
FR1500FRDW	1496mm (5ft) x 26mm	Daylight White 5500K (DW)	2150	23W	Optional
FR1800FRNW	1764mm (6ft) x 26mm	Natural White 4500K (NW)	2300	28W	Optional
FR1800FRDW	1764mm (6ft) x 26mm	Daylight White 5500K (DW)	2420	28W	Optional
FR2400FRNW	2374mm (8ft) x 26mm	Natural White 4500K (NW)	3100	36W	Optional
FR2400FRDW	2374mm (8ft) x 26mm	Daylight White 5500K (DW)	3265	36W	Optional

Other product options (lead-time & minimum order quantity applies)

Accessories

Freezer Version (silicon coated)

4W 3hr Emergency Lighting Unit (4.2)

BUS Control (dimnable)