

Adjustable Commercial Downlights



The Light Footprint Commercial Downlight range is designed to offer an alternative to the traditional metal halide / halogen high power spot fittings.

The downlights are manufactured to the highest possible standards allowing for optimal levels of light output combined with efficient heat management and maximum longevity.

These luminaires are constructed using die-cast aluminium with a white powder coat finish.

The fittings can be rotated up to 330° and tilted up to 45° for accurate spotlighting.

Technical Specification

Total Circuit Wattage 30W/40W

Working Voltage 100-265VAC

Working Temperature -10°C/+45°C

Beam Angle 20°/40°

Estimated Life Span 50,000hrs L80

CRI >82

IP Rating IP20

Power Factor >0.92

Test Standards

EN 55015:2006+A1:2007+A2:2009

EN 61547:2009

EN 61000-3-2:2006+A1:2009+A2:2009

EN 61000-3-3:2008

EN 60598-1:2008+A11:2009

EN 60598-2-2:1996+A1:1997

EN 62031:2008

EN 61347-1:2008+A1:2011

EN 61347-2-13:2006

EN 62471:2008

EN 62493:2010



5 Year Warranty L80

Product Code	Size	Colour	Lumen	TCW
ACD30NW	D.160mm / Cut-out 145mm	Natural White 4000K (NW)	1985	30W
ACD30DW	D.160mm / Cut-out 145mm	Daylight White 5500K (DW)	2090	30W
ACD40NW	D.190mm / Cut-out 165mm	Natural White 4000K (NW)	3363	40W
ACD40DW	D.190mm / Cut-out 165mm	Daylight White 5500K (DW)	3540	40W

Notes

Please be aware this product is lead time only. Minimum order quantity applies.