

# Smart Warehouse Luminaires



The Light Footprint Warehouse Luminaires provides a soft bright and flicker free light, whilst saving on energy consumption. Assembled with high grade Samsung 5630 LED's to ensure optimal light output combined with minimal degradation and high colour rendering index.

Built with reliability and longevity in-mind, this makes them perfect to replace conventional commercial/industrial lighting with high ceilings.

They are easy to install and will deliver high brightness output, low power consumption, dramatically reducing your energy bills and maintenance costs. For added safety Light Footprint luminaires are equipped with Thermo-shutdown, overload and power surge protection.

This luminaire comes with a 0–10V BUS control wire to the driver which allows the fitting to be dimmed when paired with a compatible control. Please contact us for further information.

Product Code	Size mm (L x W x H)	Colour	Lumens	Power	Dimmable
WLU1200NWD	1235 x 168 x 80	Natural White (4000k)	4750	40W	Yes (0-10V)
WLU1200NDWD	1235 x 168 x 80	Daylight White (5800k)	5000	40W	Yes (0-10V)
WLU1500NWD	1525 x 168 x 80	Natural White (4000k)	5280	50W	Yes (0-10V)
WLU1500NDWD	1525 x 168 x 80	Daylight White (5800k)	5500	50W	Yes (0-10V)

**Other product options** (lead-time & minimum order quantity applies)

60° Degree Beam Angle available

## Technical Specification

Total Circuit Wattage 20W/22W/23W/25W

Working Voltage 100–265VAC

Working Temperature -20°C/+50°C

Beam Angle 90°

Estimated Life Span 50,000hrs

CRI >80

IP Rating IP44

Power Factor >0.90

## Test Standards

EN 55015:2006+A2:2009

EN 61547:2009

EN 61000-3-2:2006+A2:2009

EN 61000-3-3:2008

EN 60598-1:2008+A11:2009



**5 Year Warranty**

**DIMMABLE (BUS 0-10V)**

## Accessories

4W 3hr Emergency Lighting Unit (4.2)

A full range of 0–10V controls